



MATERIAL SAFETY DATA SHEET

In accordance with the National Occupational Health and Safety Commission (NOHSC) criteria, BGC Fibre Cement products are not classified as hazardous materials.

Identification:-

| | |
|---|---|
| Product Name: | Duraliner Plus / Durasheet / Duratex / Duralattice / Duralux Plus / Duraplank/ Ultraform / Compressed / Ceramic & Vinyl Underlays / Nuline Plus / Duragrid/ Durascap/ Duragroove/Stonesheet/ Stratum/ Stratum Duo/Stratum Contour/Stratum Era/Durafloor |
| Other Names: | Fibre Cement Sheets |
| Manufacturer's Product Code: | Duraliner Plus / Durasheet / Duratex / Duralattice / Duralux Plus / Duraplank/ Ultraform / Compressed / Ceramic & Vinyl Underlays / Nuline Plus / Duragrid/ Durascap/ Duragroove/Stonesheet/ Stratum/ Stratum Duo/Stratum Contour/Stratum Era/Durafloor |
| UN Number: | None allocated |
| Dangerous Goods Class & Subsidiary Risk: | None allocated |
| Hazchem Code: | None allocated |
| Poisons Schedule Number: | None scheduled |
| Uses: | Fibre cement sheets for use on internal / external wall linings and soffits, also ceramic and Vinyl / Cork Underlays |

Physical Description/Properties:-

| | |
|--|--|
| Appearance: | Blue tint on face of the Duratex, a white tint to the face of 4.5, 6.0, 9.0 and 12mm Compressed while all other products are cement grey finish. |
| Boiling Point: (°C) | Not applicable |
| Vapour Pressure: | Not applicable |
| Specific Gravity (H₂O = 1) | Not relevant |
| Flashpoint: | Not applicable |
| Flammability Limits: | Not flammable |
| Solubility in water: | Not relevant |
| Reactivity (e.g. with air or water): | Not reactive |
| Auto-ignition Temperature (°C): | - |
| Odour Threshold: | Slight cement odour |
| Lower Explosion Limit: | - |
| Upper Explosion Limit: | - |
| Self accelerating Decomposition: | - |

Ingredients

| Chemical Name: | CAS Number: | Proportion: | Exposure Limits |
|--|-------------|-------------|--|
| Cement (Calcium silicate) | 66997-15-1 | > 30% | 10.0 mg/m ³ measured as inspirable dust |
| Sand (Crystalline Silica) | 14808-60-7 | > 50% | 0.1 mg/m ³ measured as inspirable |
| Paper pulp (Cellulose) | 9004-34-6 | < 8% | 10 mg/m ³ measured as inspirable dust |
| Aluminium Trihydroxide (Hydrated Ground Alumina) | 21645-51-2 | < 5% | 10 mg/m ³ measured as inspirable dust |

HEALTH HAZARD INFORMATION

The potential health hazards are related to dust generated from these materials during the use of power tools and sanding. Inhaling dust liberated from BGC Fibre cement may aggravate pre-existing respiratory conditions. The intact BGC Fibre cement does not give off dust or fume during installation or when installed. However, cutting, breaking, drilling or sawing the boards may generate dust.

Health Effects

Acute:

Swallowed:

Unlikely to occur, however may result in symptoms of acute indigestion.

Eye:

Excessive dust may cause eye irritation.

Skin:

The dust, particularly in association with heat and sweat, can cause irritation, but it is not absorbed through the skin.

Inhaled:

Inhaled dust may cause nasal, throat and lung irritation, symptomatic through excess mucus and coughing.

Chronic:

Inhaled:

If respirable crystalline silica levels are not controlled, repeated exposure to excessive dusts of fibre cement products could result in the chronic

lung disease Silicosis. However, if the practices noted in this MSDS are followed during cutting and sanding, exposure to airborne dusts should be within recommended occupational exposure standards and no long-term effects are expected.

First Aid

Swallowed:

Give copious amounts of water to drink.

Eye:

Flush thoroughly with flowing water for at least ten minutes. If symptoms persist, seek medical attention.

Skin:

Wash thoroughly with soap and water.

Inhaled:

Remove to fresh air.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

BGC Fibre Cement has adopted the following maximum exposure limits, corresponding to the limits set out by the CoA, NOHSC; Exposure Standards for Atmospheric Contaminants in the Occupational Environment:-

Exposure Standards:

- Calcium silica: 10 mg/m³ time-weighted average (TWA) as inspirable dust
- Cellulose: 10 mg/ m³ TWA as respirable dust
- Crystalline silica (quartz): 0.1 mg/ m³ TWA as respirable dust
- Aluminium Trihydroxide: 10 mg/m³ time-weighted average as inspirable dust

BGC Fibre Cement recommends keeping exposures to dust as low as practicable and work in a well-ventilated space.

Engineering Controls:

No dust is generated, unless the fibre cement is cut. Keep exposures to dust as low as practicable, preferably below 5 mg/m³ TWA (time-weighted average) of inspirable dust, to prevent respiratory discomfort. Work in the open air or near external openings in the building, for adequate ventilation. Where dust is generated, in confined spaces, local mechanical ventilation should be used, to direct the dust away from the work areas. Personal protective equipment should be used in confined spaces and where dust levels exceed the maximum levels. Use safe work practices to minimize dust release and exposure. Clean work areas regularly by wet sweeping or vacuuming with a HEPA filtered vacuum.

Ventilation:

Where safe work practices, adequate engineering and material handling controls are in place, ventilation is not normally required. Use local mechanical ventilation and or dust extraction in confined areas and where dust could escape into the working environment.

Tools and Equipment;- Repair / Maintenance

Vacuum and or wipe down all tools and equipment prior to maintenance and repair work. Avoid compressed air cleaning where possible, and wear eye and respiratory protection, and clothing as listed below.

Personal Protection:

Use personal safety protection at all times.

| | |
|-------------------------|--|
| Skin Protection: | Avoid direct skin contact with fibre cement products. Wear loose appropriate clothing, such as long sleeved shirts and long trousers, head protection and standard duty leather or equivalent gloves, which comply with Australian Standard AS 2161: Industrial Safety Gloves and Mittens. Wash work clothes regularly and do not shake out dust. |
| Eye Protection: | Wear dust resistant non-fogging safety goggles or glasses, which comply with Australian and New Zealand Standard AS/NZS 1336: Recommended Practices for Eye Protection. |
| Respiratory Protection: | Where safe work practices, adequate engineering and material handling controls are in place and used none may be required. However, BGC Fibre Cement suggests that L or M particulate respirator (dust mask), which comply with Australian and New Zealand Standard AS/NZS 1715: Selection, Use and Maintenance of Respiratory Protective Devices, and Australian and New Zealand Standard AS/NZS 1716: Respiratory Protective Devices when Exposed to Dust), be used at all times. |
| Personal Hygiene: | Do not smoke whilst handling and working with fibre cement. Wash dust from skin with mild soap and water after working with fibre cement. |
| Flammability: | Fibre cement products are non-combustible and non-flammable |

SAFE HANDLING INFORMATION

| | |
|-------------------------|--|
| Storage and Transport: | Fibre cement sheets should be stored flat and level in a covered dry area. Lift, handle and carry fibre cement sheets on edge. All lifting should be done with a straight back and bent knees. No other special transport requirements are necessary. |
| Spills and disposal: | Use wet sweeping and/or vacuuming to clean up dust and waste. Bagged waste should be placed in containers and disposed of with other construction waste in accordance with local authority guidelines. |
| Fire/explosion hazard: | . |
| Smoking and Other Dust: | Smoking and inhalation of airborne particulates from other sources may increase the risk of lung disease. Work areas and storage areas should be deemed smoke-free zones. |

BGC Fibre Cement, Material Safety Data Sheet (MSDS) is issued in accordance with the CoA, NOHSC Guidelines and any information contained herein must not be altered, deleted or amended.

BGC Fibre Cement reserves the right to amend, publish and issue a new MSDS for any changes in NOHSC Guidelines and Regulations, product materials and / or specifications.

BGC Fibre Cement Pty Ltd accepts no responsibility, expressed or implied, for any changes made to this MSDS document, without written approval by any third party.

At the issue date, the information in the BGC Fibre Cement MSDS sheet is deemed accurate and reliable.

However, BGC Fibre Cement Pty Ltd accepts no responsibility expressed or implied, for any errors and or omissions.

The onus of determining the suitability of the information in the BGC Fibre Cement MSDS documents, in relation any particular purpose and or any specific circumstance rests with the user.

BGC Fibre Cement advises the user should seek guidance, if any uncertainty arises from the information, meaning and or interpretation of the BGC Fibre Cement MSDS sheets.

BGC (Australia) Pty Ltd
ABN 6200 5736 005 008
T/A; BGC Fibre Cement

CONTACT POINTS

For all National Australian enquiries please contact your nearest BGC Fibre Cement State Office

Western Australia

(Head Office)
BGC Fibre Cement
290 Bushmead Road
Hazelmere WA 6055

Tel: 61 8 9374 2900
Fax: 61 8 9374 2901

New South Wales

BGC Fibre Cement
233 Milperra Road
Bankstown
NSW 2200

Tel: (02) 9771 9660
Fax: (02) 9771 9870

Queensland

BGC Fibre Cement
53 Argon Street
Carole Park
QLD 4300

Tel: (07) 3271 1711
Fax: (07) 3271 1733

Victoria

BGC Fibre Cement
200 Maidstone St
Altona
VIC 3018

Tel: (03) 03 9392 9444
Fax: (03) 9392 9404

South Australia

BGC Fibre Cement
71 Frost Road
Salisbury South
SA 5106

Tel: (08) 8250 4962
Fax: (08) 8258 2612

www.bgcinnovadesign.com.au